



Features

- Switched mode design.
- DC input options: 24V, 36V, 48V, 110DC.
- Regulated output.
- Short circuit protection.
- Thermal protection.
- Fully isolated output.
- Panel mounting.
- Suitable for mobile communications and industrial applications.

Specifications

INPUT VOLTAGE:	24 VDC (18-32) 10-32 VDC (10-32) 36 VDC (30-48) 48VDC (40-64) 110VDC (72-140)
OUTPUT VOLTAGE:	See selection table.
OUTPUT CURRENT:	See selection table.
OUTPUT POWER:	Typically 160W continuous, 200W intermittent.
OUTPUT VOLTAGE ADJ:	12V (11.5-14.5), 24V (20-29).
LOAD REGULATION:	2% at nominal input voltage.
LINE REGULATION:	5% over input range.
OPERATING TEMP:	-20°C to 30°C at full load derate linearly to 60°C.
SWITCHING FREQUENCY:	Approx. 55KHZ.
NOISE:	According to CISPR14.
EFFICIENCY:	Typically 82%.
PROTECTION:	Reverse input polarity. Transorb diode at input. Overvoltage protection. Short circuit protection. Thermal protection.
RIPPLE & NOISE:	Typically 50mV pk-pk at nominal load and input voltage.
EMC:	Emission EN55014, Immunity EN50082-1
ISOLATION:	Input and output are electrically isolated from chassis and input is isolated from output. Isolation voltage - 1000 VDC
TERMINALS:	Input and output have 6.3mm push on spade terminals.
DIMENSIONS:	215 x 151 x 62mm.
WEIGHT:	1.1Kg.
BRACKETS:	Optional brackets for panel mounting of units. FCS, two per unit required.

MODEL	Input DC	Output		Out (pK)
		V	A	
9260-24/12	24V	13.2V	12A	16A
9260-24/24	24V	24V	7A	9A
9260-36/24	36V	24V	7A	9A
9260-10-32/12	12/24V	13.2V	6A	8A
9260-48/12	48V	13.2V	12A	16A
9260-48/24	48V	24V	7A	9A
9260-80/24	110V	24V	7A	9A

