

SF-700 / 1000 SERIES

DC/ AC Sine Wave Inverters: 700 ~ 1000 Watts



General Specifications

Output	230 / 240VAC (selectable)
Output Power (Continuous)	700 watts / 1000 watts
Maximum Output Power	780 watts / 1150 watts 3min
Peak Output Power	1400 watts / 2000 watts
Input Voltage-DC	12VDC , (10 ~ 16V) 24VDC (20 ~ 32V) 48VDC (42 ~ 62 V)
DC Input Over Voltage Alarm	15.5V / 31.0V / 61.0V
DC Input Overvoltage Shutdown	16.0V / 32.0V / 62.0V
DC Input Under Voltage Alarm	10.5V / 21.0V 43.0V
DC Input Under Voltage Shutdown	10.0V / 20.0V / 42.0V
Efficiency	87 ~ 92% model dependent
No Load Current Draw-700W models	0.83A @ 12V, 0.43A @ 24V 0.22A @ 48V
No Load Current Draw-1000W models	0.93A @ 12V, 0.47A @ 24V 0.31A @ 48V
Output Waveform	Resistive Load Sine Wave <3% THD
Output Voltage Regulation	±3%
Frequency	50 / 60Hz selectable
Digital Display Front panel digital display allows for selection of:	OVP, UVP, OTP, OLP, VAC, AMP, WATT, VDC, TEMP, Hz
Interface Control Port	RS-232C Remote Control -Optional
Protection	Overload, Short Circuit, Reverse Polarity (Fuse) Over / Under Input Voltage, Over Temperature
Safety	IEC60950-1
EMC	EN55022 Class B
Immunity	IEC61000-4-2,-3, -4, -5, -6, 8, -11
Operating temp.	-20°C to 50°C
Cooling	Fan Cooled: Load controlled
Dimensions / Weight	334 x 179 x 81mm 3.8kg

Features

- 700 watts & 1000 watts same package / size
- 12V, 24V & 48VDC input options
- Front panel digital display
- RS – 232C interface / remote control port / wire connection to PC
- Pure sine wave output (THD < 3%) R Load
- Output frequency : 50 / 60Hz switch selectable
- High peak power
- Over voltage & Under voltage input shutdown
- Overload and short circuit protection
- Led indicator for fault conditions
- Low input No Load current draw
- Auto shutdown prevents total battery discharge
- High efficiency up to 96%
- Advanced microprocessor

Description

The **SF-700 & SF-1000 series** offer excellent performance to price ratio, for a wide range of Industrial applications.

Front panel digital display allows for selection of:
OVP, UVP, OTP, OLP,
VAC, AMP, WATT, VDC, TEMP, Hz

Suitable for powering all types of electronic loads and products, such as laptops, vacuum cleaners, fans, fluorescent, incandescent lights, shavers, coffee makers, toasters, video games, etc.

And the 3 minute maximum output power, allows for efficient and correct start up of motors and fans.

With a range of protection features such as "Auto shutdown" that prevents total battery discharge, and the extremely low input current draw when output is not powering equipment, ensures maximum battery capacity at all times.

Output voltage is user selectable: 220/230/240V RMS ± 3%, allowing for the best setting for customer equipment.

Options

Output Voltage 110/115/120V 60Hz models:
Consult sales office for complete part no / model

- **Instruction manual and further details available from our website.**

Model	Input Voltage	Output Voltage	Power Cont	Power Peak
SF-PSW1270E	12V	230 / 240VAC	700W	1400W
SF-PSW2470E	24V	230 / 240VAC	700W	1400W
SF-PSW4870E	48V	230 / 240VAC	700W	1400W
SF-PSW12100E	12V	230 / 240VAC	1000W	2000W
SF-PSW24100E	24V	230 / 240VAC	1000W	2000W
SF-PSW48100E	48V	230 / 240VAC	1000W	2000W

SF-700 / 1000 SERIES

DC/ AC Sine Wave Inverters: 700 ~ 1000 Watts

